



## VERAGON™ V10 MIL

**VERAGON'S V10 MIL HARNESSES HUMIDITY IN THE NATURAL AIR TO PRODUCE HIGH-QUALITY, MINERALISED DRINKING WATER, AT A LOWER COST THAN CONVENTIONAL BOTTLED SUPPLIES, WITH MINIMAL ENVIRONMENTAL IMPACT.**



Like all Veragon products, the V10 MIL (Military) has been used in the field by some of the world's most demanding commercial operators. Veragon's technology has been tried, tested and successfully deployed on operations by both the UN World Food Programme and NATO.

The V10 MIL 'Air to Water' Generator (AWG) initially draws the humid air through a filtration system before it enters the condensation chamber. This filtered air then makes contact with cold plates which cool the air to its dew point. This induces condensation of the water vapour in the air, changing it from gas to liquid. The condensed water is collected in the storage tank. The water is then purified using ozone,

or alternatively chlorine, in order to oxidise and inactivate organic and chemical impurities, as well as any bacteria present in the water.

The sanitised water is then mechanically filtered, removing unpleasant odours and tastes. The sanitised and filtered water is then mineralised via special mineralising cartridges, or, optionally, via the micro-dosage and dilution of hyper-concentrated mineral salts.

Before delivery, the water is finally cooled by a chiller which makes it pleasantly cool to drink. To avoid contamination from the tap, the last stage of treatment is the irradiation of ultraviolet rays. The quality of the

water meets standard potability requirements. Dedicated probes constantly monitor the quality of the water.

Veragon's V10 MIL produces up to 1,000 litres of water a day, under optimal conditions. This provides a viable alternative solution to wells or to other water supply systems, such as bottled water, reverse osmosis or desalination.

*All components of the V10 MIL are 'military approved' (i.e. purchased according to the document NATO - STANAG 2136 - Requirement for water potability during field operations and in emergency situations - Edition 6 - 21 March 2014 - NSA (MED) 0374 (2014) MEDSTD/ 2136).*

### AIR TO WATER - THE PROCESS



**TRIED AND TRUSTED BY THE WORLD'S LEADING OPERATORS**

## V10 MIL TECHNICAL FEATURES

<b>WATER PRODUCTION</b>	Up to 1,000 litres/day (approx. 40 litres/hour)
<b>WORKING CONDITIONS</b>	T = 17-45 °C / RH = 20-100%
<b>UNIT FRAME</b>	Stainless steel AISI 304
<b>TANK</b>	PE 900 L - polyethylene for drinking water
<b>SIZE / WEIGHT</b>	H 177 cm x W 190 cm x L 219 cm / 1,000 kg
<b>PURIFICATION</b>	UV / ozone or chlorine
<b>REFRIGERATING GAS (AIR TREATMENT)</b>	R-410C
<b>ELECTRICAL SUPPLY</b>	380 V - 50 Hz / 5 pin plug (three-phase + neutral)
<b>REQUIRED ELECTRICAL POWER SOURCE</b>	30.0 kW
<b>POWER CONSUMPTION</b>	Approx. 8.0 kW (tropicalised type) / Approx. 12.0 kW (standard type)
<b>NOISE</b>	Approx. 64 dB
<b>WATER CHILLER CAPABILITY</b>	$\Delta T = 20^\circ$ (up to external T = 50 °C)
<b>WATER QUALITY</b>	Certified drinking water
<b>COMPLIANCE WITH WATER STANDARD</b>	World Health Organization, Food and Agriculture Organization of the United Nations (Rome 2007 - D.L. 2001 n. 31 Italy)
<b>CERTIFICATION</b>	ISO9001:2008 / CE / DM174
<b>COLOUR</b>	Military Green / Sand / Grey / White

## V10 MIL MODELS

TYPE*	PURIFICATION	VERSION	CODE	BASIC EQUIPMENT
STANDARD (S) TROPICALISED (T)	OZONE (O) CHLORINE (C)	BASIC SPEC (B)	V10MIL-S-C-B V10MIL-T-C-B	Electromechanical operation, water quality monitor, hydraulic pipes and fittings in stainless steel, air filter, activated carbon block filter, mineralisation cartridges, water chiller, hydraulic and electrical preparation for packaging machine.
		TOP SPEC (T)	V10MIL-S-C-T V10MIL-T-C-T	Electromechanical, water quality monitor, hydraulic pipes and fittings in stainless steel, air filter, activated carbon block filter, mineralisation cartridges, water chiller, PLC control panel, display for alarm and vital function, hydraulic and electrical preparation for packaging machine.

\*STANDARD: T ≤ 35 °C, RH ≤ 70% TROPICALISED: T > 35 °C, RH > 70%

## V10 MIL RECOMMENDED OPTIONAL FEATURES

OPTIONAL FEATURE	DESCRIPTION	CODE
MICRO-DOSAGE MINERALISATION SYSTEM	The Micro-Dosage Mineralisation System (MMS) automatically checks the micro-dosage and dilution of the solution of hyper-concentrated salts, allowing the production of water with the desired mineral content.	MMS
BIOFILM PROBE	Microorganisms (pathogenic and not) may generate an organic film on the inner walls of the hydraulic circuits. The Biofilm Probe (BP) constantly monitors the state of such biofilms and the consequent change of the biocide. <i>If the machine is in a highly polluted area (e.g. industrial site), option may be deemed necessary following water testing. (Option only applicable if the units are equipped with a PLC).</i>	BP
HEAVY METAL FILTRATION SYSTEM	The Heavy Metal Filtration System (MF) ensures separation of any heavy metals from the generated water. The product is certified WRAS - DVGW for drinking water. <i>If the machine is in a highly polluted area (e.g. industrial site), option may be deemed necessary following water testing.</i>	MF
HUMAN MACHINE INTERFACE	The Human Machine Interface (HMI) enables remote control of the main functions of the generator and the treatment process via software connecting to the PLC control panel (10" colour touch display) on the machine. The software can issue alarm signals via email or telephone. <i>(Option included in top spec on request).</i>	HMI
OFF-ROAD TRAILER	The Off-Road Trailer (OT) allows transport of the AWG units, even in extreme environmental conditions.	OT



Veragon Water Solutions Ltd

8 St. James's Square, London, SW1Y 4JU, UK

Tel: +44 (0)203 858 6441 Email: info@veragonwater.com

veragon.com